TATA MOTORS Gensets

Trusted | Powerful | Durable





#HindustanKaGlobalGenset

YEARS WARRANTY ON 5 C'S **WORLD CLASS GENSET WITH**

DIESEL ENGINE OF INDIA | TATA STEEL OF INDIA I TATA STEEL LEAD ACID BATTERY OF INDIA I EXIDE **SWITCHGEARS OF WORLD | SCHNEIDER** AC GENERATOR OF WORLD | MECCALTE | STAMFORD **CONTROL PANEL OF WORLD | WOODWARD** PAINT OF WORLD I AKZONOBEL





+91 9810145225



marketing@rishabhengineering.com



www.tatamotorsgensets.com www.rishabhgenerators.com

SALIENT FEATURES

- Built for High Temperature: All The Silent Generators of Rishabh Are Designed to withstand the ambient temperature of 45 degree Celsius, though the radiators used are able to withstand ambient temperature of 50 degree Celsius.
- Sturdy: TATA Engines are most sturdy as they are originally designed for Commercial vehicle application & can go upto 5000 RPM.
- Lowest Fuel Consumption: Rishabh Generators powered by TATA engines have the lowest fuel consumption as more available power of the engine allows optimal fuel flow & there by the generator runs smoothly & efficiently.
- Widest Service Network: In India We at Rishabh | TATA Give you the most widespread Service network, with over 1800 Service dealers across India, we have the most extensive service network.
- Highest block loading capacity (70% 90%) across range which is best in Industry.
- Annual maintenance contract through our responsivservice network. Extended warranty Option available.

WORLD CLASS GENSETS

MADE IN INDIA FOR THE WORLD

Our world class Gensets come with:

India's World's India's World's India's India's India's World's World's

Diesel Engine | TATA AC Generator | STAMFORD Steel for Acoustics | TATA STEEL Foam for Acoustics | Sheela

Genset Controllers | WWOODWARD

Lead Acid Battery | A.V.M Pads POLYBOND

Switchgear | Schneider Paint |

World Class Self Starter & Dynamo | Lucus TVS ...

World Class Radiator | TATA TOYO



EVERY COMPONENT MATTERS

We at Rishabh | TATA have used the Best Components of The Industry to give you a World Class Product. Below You May Find A Sneak Peek on Some of The Major Components.

ACOUSTIC ENCLOSURE

Our Silent Gensets use India's No 1 Steel in our gensets by TATA STEEL

- Aesthetically designed, weather and sound resistant enclosure.
- Designed for Ease of Access and Serviceability.
- Acoustic Enclosures come with UV resistant powder coating which can withstand extreme weather conditions.
- Smallest Footprint giving an edge to optimize your valuable space.
- Ease of handling with appropriately located Center/ Single lifting arrangement & Forklift Slots for easy shifting.
- Inbuilt Silencer up-to 75kVA, above 75kVA Silencer Comes with Bird Protection.
- Practically located fuel filling point.
- Rishabh Silent Gensets Come with India's No.1 Sheela Foam (makers of Sleepwell Mattress).
- Certified for stringent and latest MoEF / CPCB II norms of less than 75 dB at 1 meter.
- Super Silent models for special applications which have 68-70 db sound level at 1 meter in open field conditions.
- The Foam used in enclosure is fire retardant.

GENSET CONTROLLER / SWITCHGEAR EOUIPMENT

Our Generators come with World No.1 controllers from WOODWARD

- Fault recognition by name unlike other controllers which display fault code.
- Microprocessor based.
- Brilliant & bigger best in class LCD screen.
- Lowest battery consumption in ideal condition.
- Manual Breaker operation with tactile buttons on front panel.
- Only controller giving IP 65 protection against water seepage.
- World class Daset monitoring & protection features.
- Available with Automatic & Manual Functions on demand.
- Rishabh Generators come with World No. 1 Switch gear from Schneider Electric / ABB.



Disclaimer: All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them.

TECHNICAL SPECIFICATIONS														
t.	DG Set Model	RT-25	RT-30	RT-35	RT-40	RT-45	RT-50	RT-62.5	RT-75	RT-82.5*	RT-83	RT-100	RT-125	
SET	Rating (kVA)	25	30	35	40	45	50	62.5	75	82.5*	82.5	100	125	
DG	Rating (kW)	20	24	28	32	36	40	50	60	66	66	80	100	
ACOUSTIC ENCLOSURE	Starting System		12V DC											
	Battery (Ah)	90 100												
	Canopy Size : LxBxH (mm)	2350 x 1030 x 1425					2700 x 1100x 1550				3200 x 1200 x 1800			
	Weight (Kg)	850	890	910	950	1000	1150	1250	1350	1350	1600	1700	1800	
	Fuel Tank Capacity (Ltrs)		100					11	.0		240			
	Thickness of Foam In doors		40					50				75		
	Density of Foam for Sound Insulation		32					3	8		50			
	Steel Make & Thikness in Acoustic		TATA Steel Base 3 mm Rest of Canopy 1.6 mm											
ENGINE	Engine Model Family	497SPTC							7TC		697TC			
	Engine Make	40.2	10.2					TATA 75.7 90 99.8 99.8				120 125.3 156		
	Engine Power (Bhp) Rated Speed (RPM)	40.2	48.2	56.3	56.3	56.3	/5./			99.8	120	125.3	156	
	No. of Cylinders										6			
	Bore (mm)	97	97	97	97	97	97	97	97	97	97	97	97	
	Stroke (mm)	100	100	100	100	100	128	128	128	128	128	128	128	
	Total Displacement (CC)			2960				38	00			5700		
	Lube oil Sump Capacity (Ltrs)		7 10								15			
	Total Coolant Capacity (Ltrs)	13 14 18												
	Oil Change Period	500 Hrs Or 6 Months Which Ever Is Earlier												
	Compression Ratio	17.5 : 01												
	Aspiration	Turbo Charged												
	Cooling System	Water/Coolant												
	FIP	MICO Bosch - Inline Pump									Rotary / inline numn		MICO Bosch - Inline Pump	
	Governing Type	Mech-A1 Governing									2.000.01.10000001.11.10		Mech-A1 Governing	
	Emission Norms	CPCB-II Compliant												
ALTERNATOR	Alternator Make	Meccalte Stamford												
	Type (PF)	Brushless, H Class Insulation (0.8)												
	Frequency (Hz)							50/	60					
	Voltage (V)	230/415 110/230												
	Amperes (A) @ 415 V	34	41	48	55	62	69	86	104	114	114	139	173	
CONTROLLER	Controller Make		WoodWard 1400 / 1600											
	Туре	Microprocesser Based, LCD fault display screen, Auto start / Stop Features												
	Display Parameters	Run Time Hours, Current, Voltage, Engine RPM, Frequency, Engine Temperature & Oil Pressure, Battery V, Service Due Hours, kVA, PF, KW, KWH											Battery V,	
	Modes Available		Automatic/ Manual											
	DG Protections		Unde	er/Over Fr Alt	equency ternator/	,Current V-belt, Ei	Unbalar mergen	ice, Ove cy-Off, Se	Speed, ervice D	Overloa ue Fail T	d, RWL, LLOP o Start Fail To	, HWT, LFL, Cha Stop	arging	
	мсв/мссв	SCHNEIDER / ABB												

^{*} Stand By Rating ^ Note: In View of continuous product upgradation & design changes, above specifications & dimensions are subject to change without prior notice

India's No. 1 TATA Engine

What makes TATA diesel engine India's no.1 selling diesel engine?

Maximum Power: The engines have the highest Break Horse Power (BHP) & Highest Cubic Capacity (CC) in its class.

• Environment Friendly: The engines confirm to CPCB-2 India norms having lowest emissions.

Global **Engines of India:** TATA engines are truly world class & are used by DGSET

Manufacturers Globally.

AC Generator | Alternator

Salient Features of Alternators

- Best in Class Efficiency.
- 2/3 pitch winding alternator for better handling of harmonic and un-balanced load.
- Brushless Type and insulation.
- Self-excited, self-regulated Single Bearing, Brushless & Continuous Duty.
- Protection Degree IP21/1P23.
- Inbuit DVR in most alternators



Disclaimer: All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them.

TATA MOTORS Censets

Trusted | Powerful | Durable

















#HindustanKaGlobalGenset



Manufactured By:

Authorized Goem | TATA MOTORS

K Rishabh Engineering Co. 217 Richpalpuri Opp. Hapur Morh, G. T. Road Ghaziabad, Delhi NCR-201001 India

Printed In India PG/RT/034/S25-125KVA/REC/NOV/2022/2000

Use of the material for reproduction on the internet and world web is strictly prohibited without written permission from Rishabh Engineering Co.